


| |
|---|
| zul. Radialverlagerungen ($\hat{K}r$) |
| allowable radial displacements ($\hat{K}r$) |
| bei $n = 1500 \text{ min}^{-1}$ |
| at $n = 1500 \text{ rpm}$ |
| $\hat{K}r = 3.0 \text{ mm}$ |

Drehmoment / Torque
 Zahnkranz / spider 98 Sh A-GS
 $T_{KN} = 410 \text{ Nm}$
 $T_{Kmax} = 820 \text{ Nm}$

| | |
|---|-----------------------|
| Schraubenanzugsmoment (6) M10x20 DIN 933-10.9 | $T_A = 69 \text{ Nm}$ |
| screw tightening torque (6) M10x20 DIN 933-10.9 | $T_A = 69 \text{ Nm}$ |

| | |
|--|---|
| Oberflaechenqualitaet nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2 | Schutzvermerk nach DIN 34 beachten Note protection mark acc. to DIN 34 |
| Allgemeintoleranzen nach DIN ISO 2768 - General tolerances acc. to DIN ISO 2768- | Masstab Scale: 7:10 Format DIN Size: A3 |

ROTEX 55 Ausf. 1-L=200
 ZS-DKM



| | | | | | | | | | |
|-------|----------|--------------------|--------|------------------------|----|-------------------------|--------|--------------|---|
| Datum | 25.10.00 | Werkstoff Material | DIN | Teilnummer Part number | Kz | Lfd.-Nr. Current number | 382388 | Index Change | 0 |
| Name | KO | Gewicht Weight | 12.722 | | M | | | | |