

# CLAMPEX® - Pierścień rozprężno-zaciskowy

## KTR 603 - wykonanie standardowe

### Dane techniczne



typ d x D mm	średnica wał dw mm		przenoszony moment obr. lub siła osiowa		wymiary [mm]					śruby zaciskające DIN 931 - 10.9 μcałk. = 0,14			nacisk powierzch. na wale	masa	asortyment podsta- wowy
	T Nm	F <sub>ax</sub> kN	B	B <sub>1</sub>	B <sub>2</sub>	e	d <sub>1</sub>	M	z liczba	T <sub>a</sub> <sup>1</sup> Nm	Pw N/mm <sup>2</sup>	kg			
110 x 185	75	7200	230	57	50	39	5,50	136	10	10	59	244	6,20	●	
	80	9000	250												
	85	11000	260												
115 x 188	80	8500	210	57	50	39	5,50	141	10	10	59	234	6,60		
	85	10000	240												
	90	12000	270												
120 x 215	80	10600	285	61	54	42	6,00	160	10	12	59	277	8,80		
	85	13300	314												
	90	14500	340												
125 x 215	85	11000	300	61	54	42	6,00	160	10	12	59	266	8,80	●	
	90	13000	320												
	95	15000	350												
130 x 215	90	13700	300	59	52	42	5,00	160	10	12	59	285	8,20		
	95	15800	330												
	100	18200	360												
140 x 230	95	15000	390	68	60	46	7,00	175	12	10	100	264	10,00	●	
	100	17000	420												
	105	20000	450												
155 x 263	105	20000	630	70	62	50	6,00	192	12	12	100	263	15,00	●	
	110	23000	660												
	115	26000	700												
165 x 290	115	36000	630	78	68	56	6,00	210	16	8	250	277	22,00	●	
	120	39000	660												
	125	44000	700												
175 x 300	125	40000	650	78	68	56	6,00	220	16	8	250	261	23,00	●	
	130	44000	680												
	135	49000	720												
185 x 330	135	55000	815	96	86	71	7,50	236	16	10	250	244	36,00		
	140	60000	875												
	145	65000	896												
195 x 350	140	66000	950	96	86	71	7,50	246	16	12	250	277	40,00		
	150	76000	1000												
	155	82000	1100												
200 x 350	150	74000	990	96	86	71	7,50	246	16	12	250	270	41,00		
	155	80000	1035												
	160	86000	1080												
220 x 370	160	95000	1200	114	104	88	8,00	270	16	15	250	248	54,00		
	165	102000	1300												
	170	110000	1300												
240 x 405	170	120000	1500	122	109	92	8,50	295	20	12	490	272	67,00		
	180	140000	1600												
	190	160000	1700												
260 x 430	190	165000	1700	133	120	103	8,50	321	20	14	490	262	82,00		
	200	185000	1900												
	210	205000	2000												
280 x 460	210	217000	2090	147	134	114	10,00	346	20	16	490	251	102,00		
	220	244000	2220												
	230	270000	2350												
300 x 485	230	275000	2431	155	142	122	10,00	364	20	18	490	246	118,00		
	240	295000	2567												
	245	315000	2636												

● pierścienie z asortymentu podstawowego  
dla pozostałych rozmiarów wydłużony czas dostawy